OIL MIST LUBRICATION (AIR-OIL MIST)

AGP-DG10 | Electric drive Type



AGP - DG10
① ②

① ARYUNG Grease pump
② Pump classification / ポンプ分類

- **AGP-DG10 type is a small electric fixed-quantity grease pump, suitable for short-distance lubrication. It is possible to lubricate several places in combination with a fixed-type distribution valve (PVG type).**
  AGP-DG10タイプは、短距離潤滑に適した小型電動定量グリースポンプです。 固定式分配弁（PVG式）と組み合わせて、複数箇所の注油が可能です。

- **AGP-DG10 type is a cartridge exchange type grease pump that does not have the mess and hassle caused by refilling of grease, allows quick and convenient cartridge exchange, and maintains an economical and clean environment.**
  AGP-DG10タイプは、グリースの補充による煩わしさや 煩わしさを解消し、迅速で便利なカートリッジ交換が可能で、経済的でクリーンな環境を維持するカートリッジ交換式 グリースポンプです。

- **For AGP-DG10-C, the stop time and discharge time are controlled by the digital controller built into it, and the oil supply is automatically performed at the set time.**
  AGP-DG10-Cの場合、停止時間と吐出時間は内蔵のデジタルコントローラで制御し、設定した時間に自動的に給油します。

- **It has a wide range of applications such as injection molding machines and various industrial machines.**
  射出成形機や各種産業機械など幅広い用途があります。

PUMP SPEC'

Type	Discharge volume 吐出量 cc/min	Working pressure 使用圧力 MPa	Pressure range 圧力範囲 MPa	Cartridge capacity 容量 ℓ	NLGI No. 主導	Outlet 吐出口 PT	Controller 制御装置	Net weight 重量 kg	DC24V Motor Output 出力 W	DC24V Current 電流 A
DG10	10	10.0	6-10	0.7	#000-1	1/8"	3.9	3.9	20	1.4

Appearance | 外観

